

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number  
**WO 2005/074296 A1**

(51) International Patent Classification<sup>7</sup>: **H04N 7/26,**  
G06F 17/30

(21) International Application Number:  
PCT/IB2004/004313

(22) International Filing Date:  
28 December 2004 (28.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
04300005.8 5 January 2004 (05.01.2004) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BURAZEROVIC, Dzevdet** [NL/FR]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 Paris (FR). **BARBIERI, Mauro** [IT/FR]; c/o Société Civile SPID, 156 Boulevard Haussmann, F-75008 PARIS (FR).

(74) Agent: **LANDOUSY, Christian**; Société Civile SPID, 156 Boulevard Haussmann, F-75008 Paris (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR,

[Continued on next page]

(54) Title: CODING METHOD AND CORRESPONDING CODED SIGNAL



(57) Abstract: The invention relates to a coding method applied to digital video data available in the form of a video stream consisting of consecutive frames. These frames, divided into macroblocks, include at least I-frames, independently coded, or P-frames, temporally disposed between said I-frames and predicted from at least a previous I- or P-frame, or B-frames, temporally disposed between an I-frame and a P-frame, or between two P-frames, and bidirectionally predicted from at least these two frames between which they are disposed, said predictions of P- and B-frames being performed by means of a weighted prediction with unequal amount of prediction from the past and the future. According to the invention, this coding method comprises the following steps : a structuring step, provided for capturing coding parameters characterizing the said weighted prediction ; a computing step, for delivering statistics related to said parameters ; an analyzing step for determining a change of preference regarding the direction of prediction ; a step provided for detecting the occurrences of gradual scene changes ; a step provided for generating description data of said occurrences ; and a step for encoding the description data thus obtained and the original digital video data.

WO 2005/074296 A1



HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG)

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report